

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 September 2002 (06.09.2002)

PCT

(10) International Publication Number
WO 02/069253 A1

(51) International Patent Classification⁷: **G06M 1/04**, 1/16

(21) International Application Number: PCT/GB02/00813

(22) International Filing Date: 22 February 2002 (22.02.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0104558.2 23 February 2001 (23.02.2001) GB

(71) Applicant (for all designated States except US): **BESPAK PLC** [GB/GB]; Bergen Way, North Lynn Industrial Estate, King's Lynn, Norfolk PE30 2JJ (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **OUYANG, Tian-hong** [US/US]; 161 Kingston Drive, Chapel Hill, NC

27514 (US). **BRACE, Geoff** [US/US]; 3421 Savan Court, Raleigh, NC 27613 (US).


(74) Agents: **ALEXANDER, Thomas, Bruce** et al.; Boulton Wade Tennant, Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,

[Continued on next page]

(54) Title: DOSAGE COUNTING DEVICES



(57) Abstract: Apparatus comprising a housing (1) defining a (2) portion for receiving in use a dose-dispensing container (20), the housing containing a dose counter comprising at least one annular counter member (141, 142), a helix-like coil (143) and transmission means (144) for operatively connecting the helix-like coil and the at least one annular counter member, wherein movement of the received dose-dispensing container acts to compress the helix-like coil to thereby rotate the transmission means and the at least one annular counter member.

WO 02/069253 A1



GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

- 1 -

DOSAGE COUNTING DEVICES

The present invention relates to counting devices for use with dose-dispensing delivery apparatus which require an axial force for operation.

It has been recognised that there is a need to provide accurate information to the user of a dose-dispensing delivery apparatus concerning the number of doses delivered from, or remaining in, the apparatus. Without such accurate information there is the danger that a user will forget how many doses have been delivered and hence take a greater or fewer number of doses than is required. There is also the danger that a user may be unaware that the delivery apparatus is empty or close to empty. Hence, in an emergency situation, the user may seek to take a dose from the delivery apparatus only to find that there are no doses left in the apparatus. This is especially dangerous where the delivery apparatus is for use in dispensing medicinal compounds for the treatment of chronic or acute symptoms, for example, as in the case of a pressurised metered dose inhaler used for treating asthmatic reactions.

A number of devices have been proposed to count the number of doses delivered or remaining in a delivery apparatus. WO95/08484 teaches a dose counting device for use with an aerosol medication dispenser. The device works by translating a non-rotative force on an outer cover into a rotation of an indicator wheel by use of a set of flexible pawls engaged with a set of teeth. The pawls depress and thereby extend circumferentially when the applied force forces them to effect a rotation of the teeth. This device has, however, been found to have disadvantages. The reliability of operation of the counting device depends on the relationship between the stiffness of the internal spring bias of the

- 2 -

medication dispenser and the pawls. If the pawls are too stiff relative to the internal spring bias then the medication dispenser may dispense a dose before the pawls flex sufficiently to rotate the indicator wheel; a dose would be delivered without the counter registering it. Alternatively, if the pawls are too flexible relative to the internal spring bias then the pawls may flex sufficiently to rotate the indicator wheel before the medication dispenser has dispensed a dose; a dose would be registered by the counter but not actually delivered.

The present invention seeks to provide a dosage counting device which overcomes these problems.

Accordingly, the present invention provides apparatus comprising a housing defining a portion for receiving in use a dose-dispensing container, the housing containing a dose counter comprising at least one annular counter member, a helix-like coil and transmission means for operatively connecting the helix-like coil and the at least one annular counter member, wherein movement of the received dose-dispensing container acts to compress the helix-like coil to thereby rotate the transmission means and the at least one annular counter member.

The present invention also provides apparatus comprising a housing defining a portion for receiving in use a dose-dispensing container, the housing containing a dose counter comprising at least one annular counter member, a helix-like coil and transmission means for operatively connecting the helix-like coil and the at least one annular counter member, and a support for supporting the at least one annular counter member, helix-like coil and transmission means in proper alignment with the received dose-dispensing container, wherein the support is an interference fit in the housing such that a first actuation of the received dose-dispensing

- 3 -

container sets the position of the support relative to the received dose-dispensing container and housing.

An embodiment of the present invention will now be described, by way of example only, with reference
5 to the accompanying drawings, in which:

Figure 1 is a cross-sectional view of a dispensing apparatus according to the present invention; and

10 Figure 2 is an exploded perspective view of part of the dispensing apparatus of Figure 3.

In the following description, the invention will be illustrated, by way of example only, with respect
15 to a pressurised dispensing container capable of delivering successive doses of a product in an aerosol form.

Figures 1 and 2 illustrate a dispensing apparatus according to the present invention.

20 The dispensing apparatus comprises a housing 1 having a cylindrical portion 2 with upper and lower ends. The upper end 6 is open whilst the lower end is closed off by a basal wall portion 7. A mouthpiece 3 which communicates with the cylindrical portion 2,
25 depends laterally from the lower end of the cylindrical portion 2. The mouthpiece 3 defines an outlet duct 4 which terminates in an outlet 5 of the mouthpiece 3.

An inwardly directed valve stem receiving block 9
30 is integrally formed with the basal wall portion 7 and has its longitudinal axis aligned co-axially with a longitudinal axis of the cylindrical portion 2 of the housing 1. The valve stem receiving block 9 defines a receiving bore 12 which is open to the cylindrical
35 portion 2 and an orifice 10 which is open to the outlet duct 4 of the mouthpiece 3. The receiving bore 12 and orifice 10 are linked by a duct 11.

- 4 -

Eight circumferentially spaced inwardly directed longitudinal ribs 14 are provided on the internal wall of the cylindrical portion 2.

5 In use a pressurised dispensing container 20 is received in the cylindrical portion 2. The pressurised dispensing container 20 comprises a canister body 21 defining a storage chamber for housing the product to be dispensed. The canister body 21 is closed off at one end by a metering valve
10 (not shown) having a valve stem 22 which extends externally from the metering valve. The metering valve is retained in the canister body by a crimped ferrule 23.

When the pressurised dispensing container 20 is
15 inserted into the housing 1, the valve stem 22 is received in receiving bore 12 of the valve stem receiving block 9. An annular air gap 13 exists between the internal wall of the cylindrical portion 2 and the canister body 21 to allow air to flow through
20 the dispensing apparatus in use.

According to the present invention, a dosage counter is provided comprising first and second indicator wheels 141, 142, a helical coil 143, drum 144 and support 146. The first and second indicator
25 wheels 141, 142 comprise indicia 147 marked on their peripheral walls. The first indicator wheel 141 denotes numerical 'units' and the second indicator wheel 142 denotes numerical 'tens'. Each indicator wheel 141, 142 is annular.

30 Each indicator wheel 141, 142 comprises a series of external teeth 148, 151 arranged around an upper half of the external rim of the annulus. In addition, each wheel 141, 142 comprises a series of internal teeth 149, 152 arranged around a lower half of the
35 internal rim 200 of the annulus. The first indicator wheel 141 also comprises two diametrically opposed radial notches 150 on the upper half of the internal

- 5 -

rim 200 of the annulus. More than two notches 150 may be provided.

The helical coil 143 comprises an upper ring 153 and a lower ring 154 which are interconnected by two
5 flexible helical struts 155. The upper ring 153 comprises four equi-spaced radially outwardly directed protrusions. The aperture defined by the lower ring is shaped to form a key-way 157.

The drum 144 comprises a generally cylindrical
10 body 158 having two diametrically opposed pairs of upper and lower flexible arms 160, 159 depending therefrom. An internal surface of the body 158 comprises four longitudinal recesses 161.

The support 146 comprises a generally annular
15 base 162 from which there extends upwardly a central spigot 163 and three equi-spaced circumferentially arranged guide arms 169. The spigot 163 is shaped to form a key 164. Each of the vertical guide arms 169 comprises an inwardly directed flange 170 at its
20 upper, distal end.

A lens unit 171 is provided dependent from the support bore 162.

A lower ratchet 165 and an upper ratchet 167 extends upwardly from the support base 162. Each
25 ratchet 165, 167 is provided with a ramped surface 166, 168. Six notches 172 are arranged around the periphery of the support base 162.

On assembly, the first and second indicator wheels 141, 142, are received over the spigot 163 of
30 the support base 162. The drum 144 is received within the central apertures of the two indicator wheels 141, 142. The helical coil 143 is received over spigot 163 with the key 164 of the spigot 163 engaging the key-way 157 of the lower ring 154 of the helical coil 143
35 so as to prevent relative rotation of the support base 162 and lower ring 154. The protrusions 156 of the upper ring 153 are slidably received in the

- 6 -

longitudinal recesses 161 of the drum body 158. The guide arms 169 and flanges 170 act to retain the components in axial alignment.

5 The support 146 is inserted in the cylindrical portion 2 of the housing 1 such that the longitudinal ribs 14 are engaged in the notches 172 of the support base 162 so as to prevent relative rotation therebetween.

10 The support 146 is positioned lowermost with the other components of the dosage counter being located between the support base 162 and the leading face 24 of the ferrule 23.

In use, a user operates the pressurised dispensing container 21 by depressing the canister
15 body 21 axially to move it relative to the cylindrical portion 2 of the housing 1. As a result, the valve stem 22 is inwardly retracted relative to the metering valve such that a dose of product is dispensed from the valve stem 22 into the bore 12 and duct 11 of the
20 valve stem receiving block 9. The product is then channelled by duct 11 and dispensed as an aerosol through orifice 10 into the outlet duct 4. The aerosol is inhaled by a user inhaling on outlet 5 of the mouthpiece 3.

25 The support 146 is a push-fit within the cylindrical portion 2 of the housing 1 and does not move axially during a normal operating cycle. Axial movement of the leading face 24 of the ferrule 23 is transmitted to the upper ring 153 of the helical coil
30 143. The upper and lower rings 153, 154 move towards each other and at the same time, due to the helical struts 155, the upper ring 153 rotates relative to the lower ring 154 which cannot rotate relative to the support base 162 due to the engagement of the key 164
35 and key-way 157.

As the upper ring 153 rotates, it also rotates the drum 144 due to the engagement of the protrusions

- 7 -

156 in the longitudinal recesses 161. As shown in Figure 2, the drum is moved to rotate in an anti-clockwise direction.

5 In the assembled positions, the lower arms 159 of the drum 144 are aligned with the internal teeth 149 of the first indicator wheel 141. The upper arms 160 are partially aligned with the internal teeth 152 of the second indicator wheel 142 and partially aligned with the upper half of the internal rim 200 of the
10 first indicator wheel 141. Hence, the lower arms 159 are always engaged with the internal teeth 149 of the first indicator wheel 141 but the upper arms 160 are normally held out of engagement with the internal teeth 152 of the second indicator wheel 142 due to the
15 presence of the internal rim 200 of the first indicator wheel 141.

Consequently, initially when the drum 144 rotates only the first indicator wheel 141 is incrementally rotated.

20 After successive rotations of the first indicator wheel 141, the upper arms 160 are brought into alignment with the radial notches 150 of the first indicator wheel 141. As a consequence, the upper arms 160 can flex radially outwards so as to engage the
25 internal teeth 152 of the second indicator wheel 142. Consequently, the second indicator wheel 142 rotates one increment on the next actuation of the metering valve. In this way, the 'tens' indicia can be incremented once for every ten increments of the
30 'units' indicia.

On release of the canister body 21 by the user, the pressurised dispensing container 20 returns to its rest position due to the internal spring bias of the metering valve. At the same time, the helical coil
35 143 recovers to its original shape rotating the drum 144 clockwise. The indicator wheels 141, 142 are prevented from rotating clockwise by the action of the

- 8 -

lower and upper ratchets 165, 167 on the external teeth 148, 151 of the first and second indicator wheels 141, 142 respectively.

5 The dosage counter is 'set' in the housing 1 on the first actuation as follows:

The support 146 is assembled in the cylindrical portion 2 of the housing 1 at a point above its normal operating position, i.e., nearer the open end 6 of the housing 1 than shown in Figure 1.

10 Consequently, the first and second indicator wheels 141, 142, helical coil 143 and drum 144 are all also nearer the open end 6 than their normal operating positions. On the first actuation, which may be undertaken by the user or at the point of manufacture or sale, the leading face 24 of the ferrule 23
15 initially axially moves the helical coil 143 without moving the support 146. Once the helical coil 143 has been completely compressed and the drum 144 incrementally rotated (during which movement the metering valve is actuated), the user, pharmacist or
20 manufacturer applies a higher axial force to the canister body 21 to move both the helical coil 143 and support 146 axially until the retracted valve stem 22 'grounds' against the base of the receiving bore 12 of the valve stem receiving block 9. The support 146 is
25 now in its normal operating position and is 'set'. The setting of the support 146 takes into account any variations in distance between the leading face 24 of the ferrule 23 and the end of the valve stem 22. Without this feature, it is possible for variations in
30 pressurised dispensing containers to mean that in certain circumstances, the metering valve may be actuated before the first indicator wheel 141 rotates or vice versa.

35

- 9 -

Claims:

1. Apparatus comprising a housing defining a portion for receiving in use a dose-dispensing container, the housing containing a dose counter comprising at least one annular counter member, a helix-like coil and transmission means for operatively connecting the helix-like coil and the at least one annular counter member, wherein movement of the received dose-dispensing container acts to compress the helix-like coil to thereby rotate the transmission means and the at least one annular counter member.
2. Apparatus as claimed in claim 1 wherein the helix-like coil comprises an upper ring, a lower ring and at least one strut spanning between the upper and lower rings.
3. Apparatus as claimed in claim 2 wherein the at least one strut is helically shaped.
4. Apparatus as claimed in any preceding claim wherein each of the at least one annular counter members comprise a first series of teeth, the transmission means comprising protrusions selectively engagable with each of the first series of teeth such that rotational movement of the transmission means causes the at least one annular counter member to rotate relative to the housing in a first direction.
5. Apparatus as claimed in claim 4 wherein the first series of teeth are formed around an inner rim of the at least one annular counter members.
6. Apparatus as claimed in any preceding claim wherein the dose counter comprises two or more annular counter members.

- 10 -

7. Apparatus as claimed in claim 6 wherein the transmission means comprises a drum having the protrusions dependent therefrom, wherein one end of the helix-like coil is rotationally fixed relative to the housing and the other end of the coil is engaged with the drum, such that movement of the received dose-dispensing container compresses the helix-like coil to thereby rotate the drum.
8. Apparatus as claimed in claim 7 wherein one of the upper or lower rings of the helix-like coil comprises at least one protrusion engageable in at least one slot formed in the drum.
9. Apparatus as claimed in any of claims 6 to 8 wherein a first annular counter member is driven to incrementally rotate in the first direction on each actuation of the received dose-dispensing container and a second annular counter member is driven to incrementally rotate in the first direction only after a pre-determined number of incremental rotations of the first annular counter member.
10. Apparatus as claimed in claim 9 wherein a bearing surface is provided forming at least part of the inner rim of the first annular counting member to selectively hold the drum protrusions out of engagement with the first series of teeth of the second annular counter member, the bearing surface comprising at least one indent allowing movement of the drum protrusions radially outwardly into engagement with the first series of teeth of the second annular counter member after a pre-determined number of incremental rotations of the first annular counter member.

- 11 -

11. Apparatus as claimed in any preceding claim further comprising a support slidably received in the housing to support the at least one annular counter member, helix-like coil and transmission means in
5 proper alignment

12. Apparatus as claimed in claim 11 wherein the support is located in a lower end of the dose-dispensing container receiving portion of the housing.
10

13. Apparatus as claimed in claim 12 wherein the support comprises at least one ratchet engagable with a second series of teeth formed on each of the annular counter members, so as to prevent rotation of the
15 annular counter members in a direction opposed to the first direction.

14. Apparatus as claimed in any of claims 11 to 13 wherein a lens is provided in the support.
20


15. Apparatus comprising a housing defining a portion for receiving in use a dose-dispensing container, the housing containing a dose counter comprising at least one annular counter member, a helix-like coil and
25 transmission means for operatively connecting the helix-like coil and the at least one annular counter member, and a support for supporting the at least one annular counter member, helix-like coil and transmission means in proper alignment with the
30 received dose-dispensing container, wherein the support is an interference fit in the housing such that a first actuation of the received dose-dispensing container sets the position of the support relative to the received dose-dispensing container and housing.

35

- 12 -

16. Apparatus substantially as hereinbefore described
with reference to and as shown in the accompanying drawings.

FIG. 2.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 02/00813

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 G06M1/04 G06M1/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 228 586 A (FUCHS KARL-HEINZ) 20 July 1993 (1993-07-20) column 4, line 64 -column 7, line 51; figures	1, 15, 16
A	EP 1 065 477 A (MICROSPRAY DELTA S P A) 3 January 2001 (2001-01-03) paragraph '0012! - paragraph '0023!; figures 1,3	1, 15, 16
A	US 5 740 792 A (WILKINSON KEN ET AL) 21 April 1998 (1998-04-21)	
A	WO 95 08484 A (SENETICS INC) 30 March 1995 (1995-03-30) cited in the application	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

24 May 2002

Date of mailing of the international search report

03/06/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Gélébart, Y

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 02/00813

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5228586	A	20-07-1993	AT 137142 T DE 59107710 D1 EP 0472915 A2 ES 2086438 T3 JP 3164229 B2 JP 5124688 A	15-05-1996 30-05-1996 04-03-1992 01-07-1996 08-05-2001 21-05-1993
EP 1065477	A	03-01-2001	IT MI991448 A1 BR 0002898 A EP 1065477 A2 US 6164494 A	02-01-2001 30-01-2001 03-01-2001 26-12-2000
US 5740792	A	21-04-1998	US 5829434 A US 5687710 A AT 177323 T AU 683036 B2 AU 5748794 A CA 2152088 A1 CN 1091321 A CZ 9501535 A3 DE 69323897 D1 DE 69323897 T2 DK 674533 T3 EP 0674533 A1 ES 2128550 T3 FI 952976 A GR 3030035 T3 HK 1008816 A1 HU 73522 A2 IL 108061 A JP 2924924 B2 JP 8500756 T KR 163472 B1 NO 952429 A NZ 259241 A PL 309401 A1 RU 2111020 C1 SG 52237 A1 SK 80695 A3 WO 9414492 A2 ZA 9309472 A	03-11-1998 18-11-1997 15-03-1999 30-10-1997 19-07-1994 07-07-1994 31-08-1994 15-05-1996 15-04-1999 04-11-1999 27-09-1999 04-10-1995 16-05-1999 16-06-1995 30-07-1999 28-04-2000 28-08-1996 10-06-1997 26-07-1999 30-01-1996 16-11-1998 18-08-1995 20-12-1996 02-10-1995 20-05-1998 28-09-1998 07-02-1996 07-07-1994 19-06-1995
WO 9508484	A	30-03-1995	US 5421482 A WO 9629278 A1 AU 688794 B2 AU 7732794 A BR 9407608 A CA 2172537 A1 CN 1133584 A , B EP 0720568 A1 JP 9502951 T WO 9508484 A1 US 5611444 A US 5718355 A US 5799651 A	06-06-1995 26-09-1996 19-03-1998 10-04-1995 14-01-1997 30-03-1995 16-10-1996 10-07-1996 25-03-1997 30-03-1995 18-03-1997 17-02-1998 01-09-1998